

SECRET/ CONTROL U. S. OFFICIALS ONLY
SECURITY INFORMATION

25X1A

German Democratic Republic

FDD Abstract

SHIPYARDS IN THE GDR

25X1X

(lp; German; undated)

This document is a chart concerning various shipyards in the GDR. Although undated, it may be assumed that the time referred to is after 1948 since the designation VEB (People-Owned Enterprise) occurs. The chart has the following headings (the figures refer to column numbers):

1. Register Number of the Shipyard
2. Name of Shipyard
3. Owner
- Specialization of the Shipyard
 4. Passenger Ships; 5. Tug boats; 6. Motorboats; 7. Steel boats; 8. Wooden boats; 9. New Ship Construction; 10. Outfitting of Small Boats
11. Number of productive Workers
12. Annual Capacity (Column 11 multiplied by 2100) in Work Hours
13. Annual Gross Production (Column 12 multiplied by 3.50) in Deutsche marks
- Capacity of the Slips
 14. Number; 15. Tons
- Annual Production Program

Repairs	30,000	6,000	1,000
16. Type; 17. large	10,000	3,000	500
hours;			
New Ship Construction			
20. 90,000 hours			

25X1A

25X1A

25X1A

[The foreign language document or a microfilm of it is available from CIA Library,

25X1A

2 April 1952

25X1A

SECRET OR DESTROY

SECRET/ CONTROL U. S. OFFICIALS ONLY
SECURITY INFORMATION

25X1A

Approved For Release 2002/01/04 : CIA-RDP83-00415R010800160005-9

Approved For Release 2002/01/04 : CIA-RDP83-00415R010800160005-9

SECRET/CONTROL - US OFFICIALS ONLY

SECURITY INFORMATION

25X1A

German Democratic Republic

FID Abstract [REDACTED]

DESCRIPTION OF A COMPRESSOR PRODUCED BY FKM HALLE/SAALE (2 pp; German; undated)

[REDACTED] 25X1A

25X1A

This document is a [REDACTED] report, [presumably part of a catalogue], compiled by FKM (Federation of People-Owned Enterprises for the Construction of Power Plant Machinery and Motors) in Halle/Saale, which gives a detailed, technical description of the low-pressure reciprocating compressor, model 521.301/2.

The compressor is used to supply compressed air in foundries, ore and coal mines, shipyards, workshops, etc. It has a capacity of 240 cubic meters per hour at a final maximum pressure of 6 atm. The compressor is a single-stage, two-cylinder, stationary, air-cooled model, FKM and is arranged in series. A detailed explanation is given of the individual parts, and of the operation, lubrication, and regulation of the compressor. It is stated that the advantages of the air-cooled compressor over those which are water-cooled are: In an air-cooled compressor, the highest degree of operational safety is guaranteed, regardless of place of installation, and a reduction of the cooling effect through pollution is impossible. An air-cooled compressor is also reliable and does not require servicing at the lowest temperatures, since the danger of the cooling water becoming frozen is eliminated.

In addition to a photograph and a diagram of different views of the compressor, the report contains a table of dimensions and capacity, which gives figures on the machine as a whole and on its individual parts.

25X1A

[Foreign language document or microfilm] [REDACTED] is available from CIA Library, ext. [REDACTED] 25X1A

25X1A

25X [REDACTED]

2 April 1952

SECRET/CONTROL - US OFFICIALS ONLY